

Product Styles and Sizes						Frame Styles			Frame Colors		Test Methods and Certifications		
Product Style	Configuration	Nominal Frame Depth	Minimum Size (tip-to-tip frame size)	Maximum Size (tip-to-tip frame size)	Flange	Integral Nail Fin	Equal Leg	White, Bronze, Clear Anodize, Black	Custom Colors	TAS 201 / 202 / 203			
										Design Pressure	Miami-Dade NOA	Florida Building Code	
Single Hung	(SH7700A)	O/X	2-3/4"	17" x 24-3/4"	53-1/8" x 84"	■	■	■	■	■	+80/-110	■	■
Horizontal Roller	(HR7710A)	OX,XO	2-3/4"	19-3/4" x 18" or 28" x 14-5/8"	76" x 76"	■	■	■	■	■	+80/-105.8 +80/-110*	■	■
		XOX 1/4-1/2-1/4	2-3/4"	42" x 18" or 53" x 14-5/8"	120" x 63"	■	■	■	■	■	+80/-106.7 +80/-110*	■	■
		XOX 1/3-1/3-1/3	2-3/4"	35-1/4" x 17" or 42" x 14-5/8"	113-5/8" x 63"	■	■	■	■	■	+80/-110	■	■
Casement	(CA740)	X	2-3/4"	18-1/2" x 17"	37" x 76" or 33-1/2" x 84"	■			■	■	+90/-130	■	■
		XX	2-3/4"	37" x 17"	74" x 63"	■			■	■	+70/-90	■	■
		XOX 1/4-1/2-1/4	2-3/4"	74" x 18"	120" x 63"	■			■	■	+70/-90	■	■
		XOX 1/3-1/3-1/3	2-3/4"	55-1/2" x 18"	111" x 63"	■			■	■	+70/-90	■	■
Awning	(AW740)	X	2-3/4"	22-1/2" x 17"	60" x 39" or 27-7/8" x 84"	■			■	■	+90/-130	■	■
Picture Window / Architectural	(PW/AR720A)	O	2-3/4"	14-1/2" x 14-1/2"	Up to 42 sq. ft.	■	■	■	■	■	+80/-110 +90/-130*	■	■
	(PW740A)	O	2-3/4"	18" x 18"	Up to 32 sq. ft.	■			■	■	+90/-130	■	■

+ Minimum/Maximum sizes may vary by shape. Refer to ClearQuote for specific shape sizes.

\* Maximum design pressure on smaller sizes.

Product Styles and Sizes					Frame Styles			Frame Colors		Test Methods and Certifications			
Product Style	Configuration	Nominal Frame Depth	Minimum Size (tip-to-tip frame size)	Maximum Size (tip-to-tip frame size)	Flange	Integral Nail Fin	Equal Leg	White, Bronze, Clear Anodize, Black	Custom Colors	TAS 201 / 202 / 203			
										Design Pressure	Miami-Dade NOA	Florida Product Approval	
Sliding Glass Door	(SGD770)	By-pass or Pocket and 90° or 135° Corners	2-track 5-1/16" 3-track 7-1/8" 4-track 9-5/32"	43" x 30"	5'0" x 8'0" panel or 4'0" x 10'0" panel			■	■	■	+90/-110 +90/-130*	■	■
	(SGD770NS)	By-pass or Pocket and 90° or 135° Corners	2-track 5-1/16" 3-track 7-1/8" 4-track 9-5/32"	43" x 30"	5'0" x 8'0" panel or 4'0" x 10'0" panel			■	■	■	+69.8/ -69.8 +90/ -90		■
	(SGD780)	By-pass or Pocket and 90° or 135° Corners	2-track 6-25/32" 3-track 9-11/32" 4-track 11-27/32"	50-3/8" x 35-3/4"	5'0" x 10'0" panel or 4'0" x 12'0" panel			■	■	■	+86.7/ -95 +105/-115*	■	■
French Door / Sidelites	(FD101H)	X	3"	20" x 36"	37-1/2" x 95-3/4"			■	■	**	+75/ -75	■	■
		XX	3"	36" x 36"	71-3/4" x 95-3/4"			■	■	**	+75/ -75	■	■
		O	3"	10-11/16" x 35-3/4"	36-3/4" x 95-3/4"			■	■	**	+75/ -75	■	■
	(FD750)	X	3-5/8"	20" x 35-3/4"	37" x 95-3/4"			■	■	■	+100/ -100	■	■
		XX	3-5/8"	35-3/4" x 35-3/4"	71-3/4" x 95-3/4"			■	■	■	+100/ -100	■	■
		O (Narrow)	3-5/8"	10-11/16" x 35-3/4"	36-11/16" x 95-3/4"			■	■	■	+100/ -100	■	■
		O (Full)	3-5/8"	18-1/2" x 35-3/4"	36-11/16" x 95-3/4"			■	■	■	+100/ -100	■	■

\* Maximum design pressure on smaller sizes.

\*\*Black is not available for this product.