

Product Styles and Sizes				Frame Styles				Glazing				Test Methods and Certifications					
Product Style	Configuration	Nominal Frame Depth	Minimum Size (actual DLO frame size)	Maximum Size (actual DLO frame size)	5/8" Flange	Integral Nail Fin**	J-Channel**	Equal Leg	Glazing Orientation	Design Pressure		Keystone Certification	Design Pressure		Miami-Dade Notice of Acceptance	Florida Product Approval	ENERGY STAR®
										AAMA A440 & ASTM E1886/1996	TAS 201 / 202 / 203		TAS 201 / 202 / 203	Miami-Dade Notice of Acceptance			
Single Hung (SH5500)	O/X Equal	3-1/2"	16-1/4" x 25-1/4"	52-1/8" x 84" 54" x 84"	■	■	■	■	Exterior	+65/-70	■	+70/-110	■	■	■	■	■
	O/X Proview	3-1/2"	16-1/4" x 28"	52-1/8" x 84" 54" x 84"	■	■	■	■	Exterior	+65/-70	■	+70/-110	■	■	■	■	■
	O/X Custom Sash	3-1/2"	16-1/4" x 26"	52-1/8" x 91-3/4" 54" x 91-3/4"	■	■	■	■	Exterior	+65/-70	■	+70/-110	■	■	■	■	■
Double Hung (DH5560)	X/X Equal	3-1/2"	16-1/4" x 26-1/2" or 17-1/2" x 24"	52-1/8" x 84" 54" x 84"	■	■	■	■	Exterior	+65/-70	■	+70/-110	■	■	■	■	■
	X/X Proview	3-1/2"	16-1/2" x 29"	52-1/8" x 75" 54" x 84"	■	■	■	■	Exterior	+65/-70	■	+70/-110	■	■	■	■	■
	X/X Custom Sash	3-1/2"	16-1/4" x 32"	54" x 84" 52-1/8" x 86-5/16"	■	■	■	■	Exterior	+65/-70	■	+70/-110	■	■	■	■	■
Horizontal Roller (HR5510)	XO / OX Equal	3-1/2"	25-1/2" x 20-1/4" or 33-3/4" x 16-1/4"	75" x 63" 75" x 72" 75" x 76"	■	■	■	■	Exterior	+65/-70 +50/-50	■ ■	+65/-70 +65/-80 +65/-110*	■ ■ ■	■	■	■	■
	XOX 1/4-1/2-1/4	3-1/2"	45-1/8" x 17" or 47-3/4" x 16-1/4"	120" x 63"	■	■	■	■	Exterior	+65/-70	■	+65/-70 +65/-110*	■ ■	■	■	■	■
	XOX 1/3-1/3-1/3	3-1/2"	35-1/4" x 17-1/4" or 38" x 16-1/4"	92" x 63" 120" x 63"	■	■	■	■	Exterior	+65/-70	■	+65/-110	■	■	■	■	■
Casement (CA5540)	XOX Custom Sash	3-1/2"	35-1/4" x 17-1/4" or 38" x 16-1/4"	140" x 63"	■	■	■	■	Exterior	+65/-70	■	+65/-110	■	■	■	■	■
	X Standard Hinge	3-1/2"	17" x 20"	36" x 71-9/16" or 34-5/16" x 75"	■	■	■	■	Exterior	+50/-50 +65/-70	■ ■	+65/-70	■	■	■	■	■
	X TrueHold Hinge	3-1/2"	17" x 20"	40" x 84"	■	■	■	■	Exterior	+65/-70	■	+70/-110	■	■	■	■	■

* Maximum design pressure on smaller sizes

** Maximum negative 70 (-70) design pressure on Integral Fin and J-Channel frame types

Product Styles and Sizes			Frame Styles				Test Methods and Certifications									
Product Style	Configuration	Nominal Frame Depth	Minimum Size (actual DLO frame size)	Maximum Size (actual DLO frame size)	5/8" Flange	Integral Nail Fin**	J-Channel**	Equal Leg	Glazing Orientation	Design Pressure	Keystone Certification	TAS 201 / 202 / 203	Miami-Dade Notice of Acceptance	Florida Product Approval	ENERGY STAR®	
Awning (AW5540)	X	3-1/2"	21-1/4" x 19-5/8"	60" x 42"	■	■	■	■	Exterior	+50/-50	■	+70/-110	■	■	■	
				52-1/8" x 42"	■	■	■	+65/-70		■	+70/-110	■				
				36" x 84"	■	■	■	+70/-110		■	+70/-110	■				
Picture Window / Architectural (PW/AR5540) (PW/AR5520)	O	3-1/2"	10" x 16"	75" x 48"	■	■	■	■	Exterior	+50/-50	■			■	■	
				96" x 63" or 84" x 72"	■	■	■	+70/-70		■						
				Up to 144" width / height	■	■	■				+80/-110	■				
				75" x 48"	■	■	■	+50/-50		■						
				96" x 63" or 84" x 72"	■	■	■	+70/-70		■						
				Up to 144" width / height	■	■	■				+80/-110	■				
Sliding Glass Door (SGD5570)	By-Pass or Pocket and 90° or 135° Corners	2-track 5-7/8" 4-track 10-5/8"	22-15/16" x 27-3/4" panel	40" x 80" panel	■	■	■	■	Exterior	+90/-90	■	+100/-100	■	■	■	
				50" x 80" panel	■	■	■	+80/-80		■	+80/-80	■				
				40" x 100" panel	■	■	■	+60/-65		■	+60/-65	■				
				50" x 100" panel	■	■	■	+60/-65		■	+49.6/-53.7	■				
French Door (FD5555)	X XX O	4-9/16" 4-9/16" 4-9/16"	20" x 74" 36" x 74" 12" x 20" or 20" x 12"	38-13/16" x 96"	■	■	■	■	Exterior	+70/-70	■	+70/-70	■	■	■	
				76" x 96"	■	■	■	+70/-70		■	+70/-70	■				
				40" x 111" or 111" x 40"	■	■	■	+70/-70		■	+70/-70	■				